

ARCHER

Asphalt Roof Coatings and Cements

PRODUCT DATA BULLETIN

A74 ASPHALT PLASTIC ROOF CEMENT

PURPOSE

Archer A74 Asphalt Plastic Roof Cement is an asphalt based roof cement designed for repairing roofs and roof flashings.

PRODUCT DESCRIPTION

Archer A74 Asphalt Plastic Roof Cement is manufactured from Type I Roofing Asphalt, non-asbestos reinforcing fibers and petroleum solvents.

APPLICATION

The surface to be repaired must be clean, dry and free of debris. Apply A74 evenly with a pointed roofer's trowel or gloved hand. A74 should be applied 1/8 to 1/4 of an inch thick and may be reinforced with glass membrane or polyester fabric to strengthen the repair. When making a permanent repair, open up the area and allow it to dry thoroughly. Clean up with mineral spirits and waterless hand cleaner.

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests, conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.

Manufactured by: R.M. Lucas Co. 3211 S. Wood St., Chicago, IL 60608 773-523-4300