

ARCHER

Asphalt Roof Coatings and Cements

PRODUCT DATA BULLETIN

A24 FIBERED ASPHALT ROOF COATING

PURPOSE

Archer A24 Fibered Asphalt Roof Coating provides an economical means of recoating and preserving smooth-surface asphalt roofs. Periodic recoating of otherwise sound built-up roofing felts can prolong service life many years. Deteriorated roofs can often be restored with the use of polyester fabric and select asphalt coatings. A24 also provides an economical means for dampproofing concrete foundation walls.

PRODUCT DESCRIPTION

Archer A24 is formulated from refined, low softening point asphalt, reinforcing fibers and petroleum solvents. Consistency is maintained to provide easy brushing qualities. All of our asphalt coatings are ready to use and do not require special preparation before use.

APPLICATION

Surface to be coated must be clean and dry. Weak, broken, cracked or blistered areas of the roof and flashings must be repaired prior to coating with A24. Blisters, which are caused by trapped moisture, must be opened and dried, then resealed using glass membrane and Plastic Roof Cement. Moisture trapped between plies of a roof will eventually reappear as a blister or a leak. Apply A24 evenly, as it comes from the container with any appropriate tool, preferably, a four knot roofing brush, at the rate of approximately three gallons per 100 square feet. Do not allow foot traffic until the coating is fully cured which will require six to eight weeks. Clean up with Lucas #125 Safe-Solve

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests, conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.